

USB3.1 Gen1(A/M-C/M) High-Flex Active Optical Cable

EPIUH71

Rev. 0.1



EverPro Technologies Company Ltd.



Revision History

Rev	Date (MM/DD/YY)	Author	Description of Changes	
1	3/28/2022	Lydia	Initial Release	

Table of Contents

1	DESCRIPTION	4
2	FEATURE	4
3	SPECIFICATION	5
4	PRODUCT DRAWING	6
	PART NUMBER	
	PACKAGE	
	APPLICATION(POSSIBLE BUT NOT LIMITED)	

1 DESCRIPTION

This product is USB3.1 Gen1(A/M-C/M) High-Flex active optical cable (AOC), it can perfectly transmit USB 2.0, USB3.1 Gen1 with excellent signal quality. Compared with the traditional copper wire, it is softer, slimmer, lighter and with perfect EMI/EMC feature. And it also has better reliability performance than copper wire.


2 feature

- 1) Support USB 2.0 (0~5m) and USB 3.0 (0~20m)
- 2) Plug and play without driver dependent
- 3) High reliability
- 4) Thinner, lighter and softer than conventional copper cable
- 5) Highly resistant to EMI and RFI
- 6) Drag chain test: 10 million cycle times

3 SPECIFICATION

Cable Length	Cable Length				
Up to 20m	Up to 20m				
Interface					
USB type-A plug – USB type-C plug	USB type-A plug – USB type-C plug				
Bandwidth					
Support U3:5Gbps (0~20m); Support U2: 480Mbps (0~5m);					
Power Delivery					
4.75~5.25V					
Power Supply					
900mA(0~10m),600mA (15~20m)					
Power Consumption (TYP.)					
110mA (5V input)					
Mechanical / Condition					
Cable diameter	4.9±0.2mm				
Bend Radius(Dynamic/Static)	75mm/40mm				
Tensile Strength (Long term/Shour term)	200N/500N				
Operating / Storage Temp	-20~+70°C/-40~+85°C				
Operating / Storage Humidity	0~85% / 0~85%				
Material					
Hybrid Cable Jacket	TPU				
Housing	Plastic				

4 PRODUCT DRAWING



5 PART NUMBER

Part Number	Description	
EPIUH71-A0C1KxxxPI	USB3.1 Gen1 A Plug to C Plug with locking screw, Plastic	
EPION/1-AUCIKXXXPI	Injection Housing, xxx=xxxmeter, for example,020=20m	

Note1: All of standard cables have Everpro LOGO. NRE is need if adding customized logo.

Note2: Lead time will be increased if need customized length.

6 PACKAGE



	长 length	宽 width	高 height
飞机盒 box	飞机盒 box 240mm		60mm
外箱 outer box	530mm	370mm	240mm

Application(Possible but not limited)

- Machine Vision Camera Extension
- Security Camera Extension
- Digital Signage and TV Wall
- Smart Digital Video Surveillance System
- Zero Client Connectivity
- Remote Storage